

Product DATA BULLETIN

Metal Medic 7057 Paint Remover

INCREASING PROFITABILITY THROUGH SOLUTIONS-DRIVEN CHEMICAL TECHNOLOGY

Description:

Metal Medic 7057 is an effective, non-chlorinated hydrocarbon-based paint remover designed for efficient stripping of a wide range of coatings. It breaks down and removes paints, varnishes, and other organic finishes without the use of chlorinated solvents, making it a safer and more environmentally responsible choice for industrial and maintenance applications. Its formulation allows for deep penetration into multiple layers of coating, ensuring thorough removal while minimizing surface damage to the underlying material.

Applications:

Metal Medic 7057 is used as is at temperatures from room temperature to 140 degrees F. It is also used to remove acetate resins and numerous other organic soils. MM 7057 is excellent for the removal of epoxy and polyurethane primers from aluminum alloys, mild steel, and cast iron by the immersion method. It is an acid-activated material and is not recommended for use on high strength steel.

Metal Medic 7710 may be added to control evaporation. 8-10 inches of MM 7710 is recommended.

PRODUCT PROPERTIES

Appearance	Amber Liquid
Specific Gravity	1.030 - 1.070
pH Concentrate	0.5 - 2.0

PACKAGING CONFIGURATIONS

- 5 Gallon Pails
- 55 Gallon Drums
- 275 Gallon Totes

STORAGE & HANDLING

- Packaged in Polyethylene Containers
- Store Inside at Room Temperature in Original Container
- Standard Chemical Handling Practices
- Shelf Life of ~2 Years in Sealed Containers

See SDS for complete safety recommendations.

1/2/2025

All sales are exclusively subject to and conditioned upon the terms and conditions of sale posted at www.janed.net and any other additional or different terms are objected to and rejected unless an authorized representative of JEL expressly agrees to them in a signed writing.