

Product DATA BULLETIN

Metal Medic 7795 Paint Remover

INCREASING PROFITABILITY THROUGH SOLUTIONS-DRIVEN CHEMICAL TECHNOLOGY

Description:

Metal Medic 7795 is a highly effective, non-chlorinated hydrocarbon-based paint remover, specifically designed for superior performance. It is intended to be used at full strength (100%) and heated to optimize its coating removal capabilities. To prevent evaporation and ensure maximum efficiency, a mineral oil seal is required. The recommended sealant is Metal Medic 7710, which, when applied in a 10-20 inch layer, effectively controls evaporation, ensuring consistent and reliable results throughout the application process.

Applications:

Metal Medic 7795 is used as is at temperatures from room temperature to 220 degrees F. It is also used to remove acetate resins and numerous other organic soils. Metal Medic 7795 is excellent for the removal of epoxy and polyurethane primers from aluminum alloys, mild steel, and case iron by the immersion method. It is an alkaline-activated material and buffered for most metals.

PRODUCT PROPERTIES

Appearance	Clear Colorless Liquid
Specific Gravity	0.975 - 1.015
pH 100% Solution	11.6 - 13.0

PACKAGING CONFIGURATIONS

- 5 Gallon Pails
- 55 Gallon Drums
- 275 Gallon Totes

STORAGE & HANDLING

- Packaged in Polyethylene Containers
- Store Inside at Room Temperature in Original Container
- Standard Chemical Handling Practices
- Shelf Life of ~2 Years in Sealed Containers

See SDS for complete safety recommendations.

1/2/2025

All sales are exclusively subject to and conditioned upon the terms and conditions of sale posted at www.janed.net and any other additional or different terms are objected to and rejected unless an authorized representative of JEL expressly agrees to them in a signed writing.